

Stitch 4737

Denim 1096

Specifications

Contents

58% polyester
27% pre-consumer recycled polyester
15% post-consumer recycled polyester

Weight

9.7 ± 1.0 oz./lin. yd.

Width

54" min. useable

Repeat

11.1" vertical | 14.3" horizontal

Treatment

stain repellent

Backing

acrylic backcoating

Treatment

stain repellent

Backing

acrylic backcoating

Cleaning Code

<p>Standard Care Label W-S. Clean with water based cleaning agents, foam or pure, water free solvents. Vacuuming or light brushing is recommended to prevent dust and soil buildup. May also be disinfected with hydrogen peroxide, alcohol, and quaternary ammonium (quat) based cleaners.</p>

Performance



Breaking Strength (ASTM D5034)

135 lbf min. warp and 235 lbf min. fill

Tear (ASTM D2261)

9 lbf min. warp and 15 lbf min. fill

Seam Slippage (ASTM D4034)

90 lbf warp and 70 lbf fill

Pilling resistance (ASTM D3511)

Class 4

Colorfastness to light (AATCC 16.3 Option 3)

Grade 4 min. at 40 hours

Colorfastness to crocking (AATCC 8)

Grade 4 min. dry & Grade 3 min. wet

Wyzenbeek Abrasion resistance (ASTM D4157)

70,000 double rubs cotton duck

Flammability

CA Technical Bulletin 117-2013 Section 1

Miscellaneous

Proudly woven in North America supporting our local communities. Application testing of this product is recommended. Colors may vary between dye lots. This is a directional fabric.

